



arch

A moving entrance. IC's arch offers a plug-and-play solution for a strong first impression. Use standalone as a gateway or build a tunnel.

Video panels and mechanics are low-weight, making arches easy to install and maintain. Arches are made with high contrast 6mm modules for beautifully crisp video images. Other sizes and resolutions are possible. Please inquire for full options.

IC Technologies stands behind the products it sells. All equipment meets US standards and includes a 2-year warranty.

PIXEL PITCH	6mm
PIXEL DENSITY	27777 / m ²
LED SHAPE	SMD
LED CONFIGURATION	1R1G1B
MODULE SIZE (mm)	1200mm x 7440mm
MODULE SIZE (inches)	47.24 x 292.91"
SCAN MODE	Constant Current Drive
WEIGHT	465kg / 1025lb
BRIGHTNESS	≥1500-1800 cd/m ²
REFRESH RATE	≥960 Hz
GRAY SCALE	≥10bit
COLORS	280trillion
VIEWING ANGLE	(H)≥120° / (V)≥120°
MAXIMUM POWER CONSUMPTION	700/m ² 64/sq.ft
AVERAGE POWER CONSUMPTION	233/m ² 22/sq.ft
AMBIENT TEMPERATURE	0~40°C
LIFE TIME	≥100000
WORK VOLTAGE	AC85~264V, 50-60Hz
IP RATING	IP54 - indoor

**Actual power consumption may vary*

**All specifications subject to change, please inquire for current specs.*

CONTACT:

888.349.8321
info@ic-technologies.tv

ic-technologies.tv

