



ring

Extremely versatile, double-sided video rings. Used standalone or combined, rings are perfect for streaming text, brand messaging and atmospheric graphics.

Ring element consists of structural housing, 6mm video panels and all necessary data and power cabling. Video panels and mechanics are low-weight, making rings easy to install and maintain. Rings are made with high contrast, black LED's for beautifully crisp video images. Other sizes and resolutions are possible. Please inquire for full options.

IC Technologies stands behind the products it sells. All equipment is ETL approved to meet US standards and includes a 2-year warranty.

PIXEL PITCH	6mm
PIXEL DENSITY	27,777 / m ²
LED SHAPE	SMD
LED CONFIGURATION	1R1G1B
MODULE SIZE (mm)	8,640mmW x 384mmH (outer) / 6,240mmW x 384mmH (inner)
MODULE SIZE (inches)	340"W x 15"H (outer) / 245"W x 15"H (inner)
SCAN MODE	Static
WEIGHT	350kg / 772lb
BRIGHTNESS	2,200 cd/m ²
REFRESH RATE	240Hz
GRAY SCALE	10bits / 4,096 level
COLORS	1.67million
VIEWING ANGLE	(H)≥120° / (V)≥120°
MAXIMUM POWER CONSUMPTION	6285W
AVERAGE POWER CONSUMPTION	3771W
AMBIENT TEMPERATURE	-20~50°C / -4~122°F
LIFE TIME	≥50000h
WORK VOLTAGE	AC90V-260V,50-60Hz
IP RATING	IP43 - indoor

**Actual power consumption may vary*

**All specifications subject to change, please inquire for current specs.*

CONTACT:

888.349.8321
info@ic-technologies.tv

ic-technologies.tv

