

LADDER V18-L specifications

PIXEL PITCH	18.75
LED BRAND	Silan
LED TYPE	3-in-1 SMD
TRANSPARENCY	40%
BRIGHTNESS IN NITS (CD/M2)	2400/3500
VIEWING ANGLE H/V	>120°
PIXEL DENSITY M2	2844
PIXEL DENSITY SQ.FT.	263
PANEL SIZE (WxHxD) MM	1200x292x13.4
PANEL SIZE (WxHxD) INCH	47.24x11.50x0.53
PANEL SURFACE IN M2	0.36
PANEL RESOLUTION (WXH)	16x64
WEIGHT PER PANEL KG/LB	3.55/21.75
WEIGHT KG-M2 / LB-SQ.FT.	9.87/2
POWER CONSUMPTION MAX/AVG PANEL	180
POWER CONSUMPTION MAX W/SQ.FT.	46
INPUT VOLTAGE	110-220
POWER CONSUMPTION MAX W/M2	500
DATA TRANSMISSION	RJ45
REFRESH RATE	1920 Hz
COLORS	68 Billion
OPERATING TEMPERATURE	-20-50°C/-4-122°F
ENVIRONMENT	IP65 (INDOOR)

**Top-of-the-line Cree LED's available as well, please inquire for more details*

All specifications subject to change, please contact us for current specs.

