

LADDER V30-L specifications

PIXEL PITCH	31.25
LED BRAND	Silan
LED TYPE	3-in-1 SMD
TRANSPARENCY	55%
BRIGHTNESS IN NITS (CD/M2)	2,400
VIEWING ANGLE H/V	>120°
PIXEL DENSITY M2	1024
PIXEL DENSITY SQ.FT.	95
PANEL SIZE (WxHxD) MM	1000x250x11
PANEL SIZE (WxHxD) INCH	39.37x9.84x0.43
PANEL SURFACE IN M2	0.25
PANEL RESOLUTION (WXH)	8x32
WEIGHT PER PANEL KG/LB	1.9/4.19
WEIGHT KG-M2 / LB-SQ.FT.	7.6/1.55
POWER CONSUMPTION MAX/AVG PANEL	70
POWER CONSUMPTION MAX W/SQ.FT.	26
INPUT VOLTAGE	110-220
POWER CONSUMPTION MAX W/M2	280
DATA TRANSMISSION	RJ45
REFRESH RATE	1920 Hz
COLORS	68 Billion
OPERATING TEMPERATURE	-20-50°C/-4-122°F
ENVIRONMENT	IP65 (INDOOR)

**Top-of-the-line Cree LED's available as well, please inquire for more details*

All specifications subject to change, please contact us for current specs.



VISIT OUR LED LAB:
475 Greenwich St.
New York, New York 10013

