

LADDER V75-L specifications

PIXEL PITCH	75
LED BRAND	Cree
LED TYPE	3-in-1 SMD
TRANSPARENCY	75%
BRIGHTNESS IN NITS (CD/M2)	1,500
VIEWING ANGLE H/V	>120°
PIXEL DENSITY M2	177
PIXEL DENSITY SQ.FT.	16
PANEL SIZE(WXHXD) MM	1200x292x13.4
PANEL SIZE(WXHXD) INCH	47.25x11.5x0.53
PANEL SURFACE IN M2	0.36
PANEL RESOLUTION (WXH)	4x16
WEIGHT PER PANEL KG/LB	1.35/2.98
WEIGHT KG- M2/LB-SQ.FT.	3.75x0.80
POWER CONSUMPTION MAX/AVG PANEL	20
POWER CONSUMPTION MAX W/SQ.FT.	5
INPUT VOLTAGE	110-220
POWER CONSUMPTION MAX W/M2	56
DATA TRANSMISSION	RJ45
REFRESH RATE	1920 Hz
COLORS	68 Billion
OPERATING TEMPERATURE	-20-50°C/-4-122°F
ENVIRONMENT	IP65 (INDOOR)

All specifications subject to change, please contact us for current specs.

