

LADDER V9-L specifications

PIXEL PITCH	9.375
LED BRAND	Silan
LED TYPE	3-in-1 SMD
TRANSPARENCY	10%
BRIGHTNESS IN NITS (CD/M2)	1,200
VIEWING ANGLE H/V	>120°
PIXEL DENSITY M2	11377
PIXEL DENSITY SQ.FT.	1053
PANEL SIZE (WxHxD) MM	1200x299x27.7
PANEL SIZE (WxHxD) INCH	47.24x11.77x1.09
PANEL SURFACE IN M2	0.36
PANEL RESOLUTION (WXH)	32x128
WEIGHT PER PANEL KG/LB	4.8/29.46
WEIGHT KG-M2 / LB-SQ.FT.	13.33/2.72
POWER CONSUMPTION MAX/AVG PANEL	180
POWER CONSUMPTION MAX W/SQ.FT.	46
INPUT VOLTAGE	110-220
POWER CONSUMPTION MAX W/M2	500
DATA TRANSMISSION	RJ45
REFRESH RATE	>960 Hz
COLORS	68 Billion
OPERATING TEMPERATURE	-20-50°C/-4-122°F
ENVIRONMENT	IP65 (INDOOR)

**Top-of-the-line Cree LED's available as well, please inquire for more details*

All specifications subject to change, please contact us for current specs.

