

FLOOR

X15-FL X20-FL X30-FL

specifications

| | | | |
|--|------------------|------------------|------------------|
| PIXEL PITCH | 15.625mm | 20.83mm | 31.25mm |
| VIRTUAL/REAL | real | real | real |
| LED TYPE | 3-in-1 SMD | 3-in-1 SMD | 3-in-1 SMD |
| BRIGHTNESS IN NITS (CD/M2) | 2500 | 2000 | 1600 |
| VIEWING ANGLE H/V | 175°/175° | 175°/175° | 175°/175° |
| PIXEL DENSITY M2 / SQ. FT. | 4,096 / 380 | 2,304 / 213 | 1,024 / 95 |
| PANEL SIZE(WXHXD) MM | 500x500x90 | 500x500x90 | 500x500x90 |
| PANEL SIZE(WXHXD) INCH | 19.69x19.69x3.55 | 19.69x19.69x3.55 | 19.69x19.69x3.55 |
| PANEL SURFACE IN M2 | 0.25 | 0.25 | 0.25 |
| PANEL RESOLUTION (WXH) | 31x31 | 24x24 | 16x16 |
| WEIGHT PER PANEL KG/LB | 14 / 31 | 13 / 27 | 13 / 27 |
| WEIGHT KG/M2 | 56 | 52 | 52 |
| POWER CONSUMPTION MAX/AVG PANEL | 310 | 160 | 85 |
| POWER CONSUMPTION MAX W/M2 - W/SQ. FT. | 1240 / 113 | 640 / 59 | 340 / 31 |
| INPUT VOLTAGE | AC220 50Hz | AC220 50Hz | AC220 50Hz |
| DATA TRANSMISSION | DVI/HDMI | DVI/HDMI | DVI/HDMI |
| PROCESSING DEPTH | 14bit | 14bit | 14bit |
| REFRESH RATE | ≤2500Hz | ≤2500Hz | ≤2500Hz |
| FRAME RATE | ≤800Hz | ≤800Hz | ≤800Hz |
| BRIGHTNESS CONTROL | Adjustable | Adjustable | Adjustable |
| COLORS | 16,384 | 16,384 | 16,384 |
| OPERATING TEMPERATURE | 0°-45°C/32-114°F | 0°-45°C/32-114°F | 0°-45°C/32-114°F |
| OPERATING HUMIDITY | 10-80% | 10-80% | 10-80% |
| ENVIRONMENT | IP65 (INDOOR) | IP65 (INDOOR) | IP65 (INDOOR) |
| MAX STATIC LOAD KG/LB | 500/1,100 | 500/1,100 | 700/1,545 |

All specifications subject to change, please contact us for current specs.

