

# FLOOR

## X15-FL X20-FL X30-FL

## specifications

|                                        |                  |                  |                  |
|----------------------------------------|------------------|------------------|------------------|
| PIXEL PITCH                            | 15.625mm         | 20.83mm          | 31.25mm          |
| VIRTUAL/REAL                           | real             | real             | real             |
| LED TYPE                               | 3-in-1 SMD       | 3-in-1 SMD       | 3-in-1 SMD       |
| BRIGHTNESS IN NITS (CD/M2)             | 2500             | 2000             | 1600             |
| VIEWING ANGLE H/V                      | 175°/175°        | 175°/175°        | 175°/175°        |
| PIXEL DENSITY M2 / SQ. FT.             | 4,096 / 380      | 2,304 / 213      | 1,024 / 95       |
| PANEL SIZE(WXHXD) MM                   | 500x500x90       | 500x500x90       | 500x500x90       |
| PANEL SIZE(WXHXD) INCH                 | 19.69x19.69x3.55 | 19.69x19.69x3.55 | 19.69x19.69x3.55 |
| PANEL SURFACE IN M2                    | 0.25             | 0.25             | 0.25             |
| PANEL RESOLUTION (WXH)                 | 31x31            | 24x24            | 16x16            |
| WEIGHT PER PANEL KG/LB                 | 14 / 31          | 13 / 27          | 13 / 27          |
| WEIGHT KG/M2                           | 56               | 52               | 52               |
| POWER CONSUMPTION MAX/AVG PANEL        | 310              | 160              | 85               |
| POWER CONSUMPTION MAX W/M2 - W/SQ. FT. | 1240 / 113       | 640 / 59         | 340 / 31         |
| INPUT VOLTAGE                          | AC220 50Hz       | AC220 50Hz       | AC220 50Hz       |
| DATA TRANSMISSION                      | DVI/HDMI         | DVI/HDMI         | DVI/HDMI         |
| PROCESSING DEPTH                       | 14bit            | 14bit            | 14bit            |
| REFRESH RATE                           | ≤2500Hz          | ≤2500Hz          | ≤2500Hz          |
| FRAME RATE                             | ≤800Hz           | ≤800Hz           | ≤800Hz           |
| BRIGHTNESS CONTROL                     | Adjustable       | Adjustable       | Adjustable       |
| COLORS                                 | 16,384           | 16,384           | 16,384           |
| OPERATING TEMPERATURE                  | 0°-45°C/32-114°F | 0°-45°C/32-114°F | 0°-45°C/32-114°F |
| OPERATING HUMIDITY                     | 10-80%           | 10-80%           | 10-80%           |
| ENVIRONMENT                            | IP65 (INDOOR)    | IP65 (INDOOR)    | IP65 (INDOOR)    |
| MAX STATIC LOAD KG/LB                  | 500/1,100        | 500/1,100        | 700/1,545        |

*All specifications subject to change, please contact us for current specs.*

