

X - FS SERIES SPECIFICATIONS

PIXEL PITCH	3.9mm	4.6mm	5.2mm
LED TYPE	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD
BRIGHTNESS IN NITS (CD/M2)	1200	1200	1200
VIEWING ANGLE H/V	160°/100°	160°/100°	160°/100°
PIXEL DENSITY M2	65536	46656	36864
PANEL SIZE(WXHXD) MM	500x500x65	500x500x65	500x500x65
PANEL SIZE(WXHXD) INCH	19.69x19.69x2.56	19.69x19.69x2.56	19.69x19.69x2.56
PANEL SURFACE IN M2	0.25	0.25	0.25
PANEL RESOLUTION (WXH)	128x128	108x108	16x16
WEIGHT PER PANEL KG/LB	7.5 / 16.55	7.5 / 16.55	7.5 / 16.55
WEIGHT KG/M2	30	30	30
POWER CONSUMPTION MAX/AVG PANEL	300/80	300/80	300/80
INPUT VOLTAGE	AC110-220 50/60Hz	AC110-220 50/60Hz	AC110-220 50/60Hz
DATA TRANSMISSION	DVI	DVI	DVI
PROCESSING DEPTH	16bit	16bit	16bit
REFRESH RATE	≤2000Hz	≤2000Hz	≤2000Hz
COLORS	281 trillion colors	281 trillion colors	281 trillion colors
DRIVING METHOD	1/16 Scan	1/16 Scan	1/16 Scan
CONTRAST RATIO	4000:1	4000:1	4000:1
LIFETIME (50% Brightness) /Hrs	100,000	100,000	100,000
BRIGHTNESS CONTROL	Adjustable	Adjustable	Adjustable

All specifications subject to change, please contact us for current specs.

