

X-5 specifications

| | |
|-------------------------------|-------------------|
| PIXEL PITCH | 5.2mm |
| LED TYPE | 3-in-1 Black SMD |
| BRIGHTNESS NITS/CD M2 | 1500-2000 |
| VIEWING ANGLE H/V | 140/100 |
| CONTRAST RATIO | 2000:1 |
| PIXEL DENSITY M2 | 36,864 |
| PIXEL DENSITY SQ.FT. | 3,426 |
| PANEL SIZE(WXHXD) MM | 500x500x105 |
| PANEL SIZE (WXHXD) INCH | 19.69x19.69x4.13 |
| PANEL RESOLUTION | 96 x 96 |
| WEIGHT PER PANEL KG/LB | 9/19.84 |
| POWER CONSUMPTION MAX W/M2 | 800 |
| POWER CONSUMPTION MAX W/Q.FT. | 74 |
| INPUT VOLTAGE | 110-240 |
| REFRESH RATE | 6,00-2,000Hz |
| DRIVE METHOD | 1/8 Scan Method |
| OPERATING TEMPERATURE | -10-40°C/32-104°F |
| OPERATING HUMIDITY | 10-90%RH |
| ENVIRONMENT | Indoor use |

**specifications subject to change, please inquire for current specs.*

